MATERIAL SAFETY DATA SHEET

PRODUCT NAME: MAXIMA PHST. HITHIDING

HMIS CODES: H F R P

PRODUCT CODE: MH-686

zu H

MANUFACTURER'S NAME: Lanco Mfg.

ADDRESS: UKB. HPONIÉ #5 SHN LORENZO PK, ØØ754

INFORMATION PHONE: (787) /36-4861 EMERGENCY PHONE: 1-800-424-9300

NAME OF PREPARER : VICTUR M. HERNHINDEZ DATE REVISED : 61-61-99

======= SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION ========

VAPOR PRESSURE WEIGHT OCCUPATIONAL EXPOSURE LIMITS MA HO & TEMP PERCENT CAS NUMBER OSHA PEL ACGIH TLV OTHER HAZARDOUS COMPONENTS N/H ΝA NNÁ 7732-18-5 N\A WATER .5 mg/m3 N/A ΝA N/A MIXTURE MICROBICIDE 8.6 OF (0.5% .1 mg/m3 .3 mg/m3 N/A MIXTURE *BIOXIDE

BOILING POINT: N/A

SPECIFIC GRAVITY (H20=1): 1.4

VAPOR DENSITY: LIGHTER THAN HIR

EVAPORATION RATE: N/A

COATING V.O.C. : 1.30 LB/GL (156 6/L) w.60 L8/6L (/≥ 6/L) MATERIAL V.O.C.:

SOLUBILITY IN WATER: AGUEOUS SYSTEM

APPEARANCE AND ODOR:

FLASH POINT: N/H

METHOD USED: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A UPPER: N/A

EXTINGUISHING MEDIA: , LOZ, WATER FOG, OTHER

SPECIAL FIREFIGHTING PROCEDURES

SUMMON PROFESSIONAL FIREFIGHTERS. USE FULL PROTECTIVE EQUIPMENT INCLUDING SELFCONTAINED BREATHING APPARATUS. WATER SPRAY MAY BEINEFFECTIVE. IF WATER IS USED, FOUNGIZLES ARE PREFERABLE.

UNUSUAL FIRE AND EXPLOSION HAZARDS

DUE TO PRESSURE BUILD- UP, CLOSED CONTAINERS EXPOSED TO EXTREME HEAT MAY EXPLODEDURING EMERGENCY CONDITIONS, OVEREXP-SURE TO DECOMPOSITION PRODUCT MAY CAUSE A HEALTH HAZARD. SYMTOMS MAY NOT BE INMEDIATELY APPARENT. OBTAIN MEDICAL ATTEN 110N.

^{*} Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

STABILITY: STABLE

INCOMPATIBILITY (MATERIALS TO AVOID)

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

MAY CAUSE HAZARDOUS FUMES WHEN HEATED TO DECOMPOSITION, FUMES MAY CONTAIN CARBOMMONOXIDE, CARBON DIOXIDE.

HAZARDOUS POLYMERIZATION: WILL NOT OLCUR

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE IRRITATION OF THE RESPIRATORY TRACT: HEADACHE, NAUSER, DIZZINESS.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE INCASE OF EYE CONTACT, FLUSH WHITH LARGE AMOUNTS OF WATER FOR AT LEAST IS MINUTES. SET MEDICAL ASSISTANT.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE REMOVE WHITH SORP AND WATER, REMOVED STILED CLOTHING.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

DRINK LOR 2 GLASSES OF WATER DILLITE. DO NOT INDUCE VOMITING. CONSULT PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY.

HEALTH HAZARDS (ACUTE AND CHRONIC)

PROLONGED AND REPEATED BREATHING OF SPHAY MIST AND/OR SANDING DUST OVER A PERIOD OF YEARS MAY CAUSE DUST DISEASE OF THE LUNGS.

CARCINOGENICITY: NTP? NU IARC MONOGRAPHS? NU OSHA REGULATED? NU NOME

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE NOW MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

EMERGENCY AND FIRST AID PROCEDURES

IF BREATHED: REMOVED TO FRESH AIR. IF IN EYES:IN CASE OF EYE CONTACT, FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST IS MINUTES. IF OF SKIM:REMOVE WITH SOAP AND WATER, REMOVED SUILED CLOTHING, INGESTION: INDUCE VONITING PROMITLY OCCORDING TO PHYSICIANS INTRUCTIONS OR BY HAVING PATIENT STICK FINGER DOWN THROAT. AFTER VONITING HAS BEEN INDUCED, GIVE TWO TEAS POOMPILS OF SAKING SODA IN WATER.

======== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE ==========

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

WASH WITH WATER, BEFORE ATTENTING CLEAN UP, REFER TO HAZARD CAUTION INFONATION IN OTHER SECTION OF THIS MATERIAL SAFETY MATA FORM, CONTAIN SPILLED MATERIAL ANDREMOVED WITH INERT ABSORBENT, STORE IN CLOSED CONTAINER.

WASTE DISPOSAL METHOD

DISPOSE OF IN ACORDANCE WITH LOCAL, STATE AND FEDERAL REGULATION.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING STORE BELOW 100 F AND KEEP FROM FREEZING, KEEP CONTAINER CLOUSED WHEN NOT IN USEDO NOT REUSE EMPTY CONTAINER, KEEP OUT OF REACH OF CHILDREN.

OTHER PRECAUTIONS MINE

RESPIRATORY PROTECTION

DO NOT BREATHE VAPORS, SPRAY MIST OR SANDING DUST. WHEN SPRAY APPLIED IN OUTDOOR OR OPEN AREASMITH UNRESTRICTED VENTILA-TION, AND DURING SANDINGOR GRINDING OPERATION, USE NICSHANSHA APROVED MACHANICAL FILTER RESPIRATOR TO REMOVE SOLID AIRB TIRNE PARTICLES OF DVERSPRAY AND SANDING BUST.

VENTILATION

USE ONLY WITH ADEQUATE VENTILATION. PROVIDE BENARAL DILUTION OR LOCAL EXHAUST. VENTILATION IN VOLUME AND PATTERN TO KEEP AIR COTAININANT CONCETRATION BELOW CURRENT APPLICABLE SAFETY AND HEALTH STANDARS IN THE MIXING.

PROTECTIVE GLOVES

NOT REQUIRED.

EVE PROTECTION

DO NOT IN EYES. SAFETY EYEMEAR WITH SPLASH GUARDS OR RECOMMENDED TO PREVENT CONTACT.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT MIT GERNINEB.

WORK/HYGIENIC PRACTICES

REMOVE AND WASH SOILED CLOTHING BEFORE REUSE. WASH HANDS BEFORE EATING, SMOKING OR USING THE BASHROOM.

DISCLAIMER

The information contained herein is based on data believed by this company to be accurate, but we do not assume any manning for its accuracy. We neither suggest nor guarantee that any hazards mentioned are the only ones which exist. The manner of that use and whether there is any infringement of patents is the sole responsability of the user.